

Australian Standard™

**Installation of nailplated timber roof
trusses**

This Australian Standard was prepared by Committee TM-002, Timber Framing. It was approved on behalf of the Council of Standards Australia on 7 April 2004 and published on 1 June 2004.

The following are represented on Committee TM-002:

Association of Consulting Engineers, Australia
Australian Building Codes Board
Australian Institute of Building
Building Research Association of New Zealand
CSIRO Manufacturing and infrastructures Technology
Engineers Australia
Forest Industries Federation (WA)
Housing Industry Association
Master Builders, Australia
New Zealand Forest Industries Council
New Zealand Forest Research Institute
New Zealand Timber Industry Federation
Plantation Timber Association Australia
Plywood Association of Australasia
South Australian Housing Trust
Structural Engineered Timber Manufactures Association, New Zealand
Timber and Building Materials Association, NSW
Timber Development Association, NSW
Timber Development Association of South Australia
Timber Merchants Association of Victoria
Timber Promotion Council
Timber Queensland

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Web Shop at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Global Standard*, has a full listing of revisions and amendments published each month.

Australian Standards™ and other products and services developed by Standards Australia are published and distributed under contract by SAI Global, which operates the Standards Web Shop.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

This Standard was issued in draft form for comment as DR 02024.

Australian Standard™

Installation of nailplated timber roof trusses

Originated as AS 4440—1997.
Second edition 2004.

COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd
GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 6041 4

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee TM/2, Timber Framing, to supersede AS 4440—1997, *Installation of nailplated timber trusses*.

The Standard is the result of a consensus among Australian and New Zealand representatives on the Joint Committee to produce it as an Australian Standard.

The objective of this Standard is to provide basic performance requirements and specifications for the bracing, connection and installation of nailplated timber trusses.

The objective of this revision is to incorporate latest technical information and performance criteria, which resulted from the continued development of timber framing systems in Australia and overseas. Reflected in this Standard, the following have been included in this revision:

- (a) Provision for limit state design methods.
- (b) Requirement for fixing to non-loadbearing external walls (Clause 2.2.3(d)).
- (c) Amendment to the definitions of bow (Clause 3.4.2) and plumb (Clause 3.4.3).
- (d) Provision for intermediate ceiling joists (Clause 3.6 and Appendix D).
- (e) Provision for internal top chord ties for north-light trusses (Clause 4.2.2.2) and top-hat trusses (Clause 4.2.2.3).
- (f) Deletion of the informative Appendix for the permanent bottom chord ties (the original Appendix G).

This Standard is intended to promote an agreement across different industries, and to replace the various installation manuals and inconsistent bracing details currently in use. It provides a unique method of bracing, connection and installation yet does not preclude the use of other methods that are approved and authorized.

Statements expressed in mandatory terms in notes to tables and figures are deemed to be requirements of this Standard.

The term 'informative' has been used in this Standard to define the application of the appendix to which it applies. An 'informative' appendix is only for information and guidance.

CONTENTS

	<i>Page</i>
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE	5
1.2 APPLICATION	5
1.3 REFERENCED DOCUMENTS	6
1.4 USE OF ALTERNATIVE MATERIALS OR METHODS	6
1.5 DEFINITIONS	6
1.6 LOADS.....	11
1.7 DOCUMENTATION AT APPROVAL STAGE AND DELIVERY	11
1.8 NAILS	11
SECTION 2 SUPPORTING STRUCTURES	
2.1 GENERAL	12
2.2 WALLS	12
SECTION 3 TRUSS INSTALLATION	
3.1 TRUSS LAYOUT.....	15
3.2 STABILITY DURING INSTALLATION	15
3.3 TEMPORARY BRACING	15
3.4 INSTALLATION TOLERANCES	16
3.5 PLASTERBOARD FIXED DIRECTLY TO BOTTOM CHORDS	17
3.6 INTERMEDIATE CEILING JOISTS	17
3.7 TIE-DOWN REQUIREMENTS	17
3.8 MULTIPLE (MULTI-PLY) TRUSS.....	17
3.9 TRUSS MODIFICATION	17
3.10 REJECTION CRITERIA	18
3.11 TRANSPORT, STORAGE, LIFTING AND HANDLING	18
SECTION 4 ROOF BRACING	
4.1 GENERAL	19
4.2 ROOF BATTENS.....	19
4.3 TOP CHORD BRACING	22
4.4 BOTTOM CHORD BRACING	37
4.5 WEB BRACING	38
SECTION 5 TRUSS CONNECTION	
5.1 GENERAL	39
5.2 HIP ENDS	39
5.3 GIRDER TRUSSES	45
5.4 VALLEY (SADDLE) TRUSSES.....	47
SECTION 6 TRUSS OVERHANGS	
6.1 STANDARD TRUSS-OVERHANGS	49
6.2 GABLE VERGE.....	50
6.3 BOXED GABLE ENDS	53
6.4 VERANDAHS.....	53
6.5 PERGOLAS	53

APPENDICES

A	DOCUMENTATION AT APPROVAL STAGE AND ON DELIVERY	54
B	RECOMMENDED PRACTICE FOR TRUSS INSTALLATION.....	56
C	RECOMMENDATIONS FOR TEMPORARY BRACING	57
D	INTERMEDIATE CEILING JOISTS AND HANGERS	60
E	TRANSPORT, STORAGE, LIFTING AND HANDLING OF TRUSSES.....	61
F	TYPICAL SPECIFICATION FOR, AND EXAMPLE OF, A STEELBRACE	63
G	FIXING DETAILS FOR TYPICAL GIRDER BRACKETS (TRUSS BOOTS)	64

STANDARDS AUSTRALIA

Australian Standard Installation of nailplated timber roof trusses

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE

This Standard specifies requirements for the bracing, connection and installation of nailplated timber trusses in roof structures for typical application.

1.2 APPLICATION

This Standard is intended to apply to nailplated timber roof trusses within the following general limitations:

- (a) Residential structures (BCA Classes 1, 2, 3 and 10) and light commercial structures.
- (b) Maximum roof pitch of 45° (100:100).
NOTE: For roof pitch greater than 35°, supporting structure may need special consideration.
- (c) Shape in plan view to be rectangular or near rectangular, or a series or combination of rectangular shapes or near-rectangular shapes, including splayed-end and boomerang-shaped buildings and the like, and projections such as bay windows.
- (d) Maximum truss span of 16 m.
- (e) Maximum truss spacing of—
 - (i) 900 mm; or
 - (ii) 1200 mm, for lightweight roofs (e.g., metal sheet roofs) in wind classification N3 or lower.
- (f) Maximum design gust wind speed of 74 m/s (wind classification C3) for ultimate limit state method in accordance with either AS/NZS 1170.2 or AS 4055.

This Standard may also be applicable to the design and construction of other classes of buildings where the design criteria, loadings and other parameters applicable to those classes of building are within the limitations of this Standard.

NOTES:

- 1 Additional limitations are also included in the relevant Clauses of this Standard.
- 2 Subject to approval, this Standard may be used for other structures similar to those specified herein.
- 3 AS 1720.1 provides for the design of timber elements within nailplated timber trusses, which is not covered by this Standard.
- 4 Roof bracing and truss connection specified in this Standard does not cover nailplated timber truss subjected to snow load.
- 5 Specifications in this Standard are applicable for use in conjunction with non-trussed hip-end components.



SAI GLOBAL

This is a free 7 page sample. Access the full version online.

The remainder of this document
is available for purchase online at

www.saiglobal.com/shop

SAI Global also carries a wide range of publications from a wide variety of Standards Publishers:



SAI GLOBAL



Click on the logos to search the database online.